Technical Data



POLYMER REMOVER HEAVY DUTY MOULD CLEANER



POLYMER REMOVER is an extremely effective and powerful solvent blend, which has been developed for use on heavily soiled moulds and dies to remove a variety of moulding deposits.

APPLICATIONS

Will assist in the removal of plastics, rubbers and resin deposits, including:

And a man and and a man and a m	* ABS	* Acetals	* Acrylates	* PVC
	* Epoxy Resins (uncured)		* Nylons	* Polyamides

- * Polystyrenes
- * Polyurethanes

* Rubbers

* Silicone Resins

Also effective on other materials such as cellulose resins and alkyd resins.

The product offers a controlled rate of evaporation for maximum efficiency. After cleaning, any residual solvent will evaporate to leave the surface clean and dry.

Apply directly onto the soiling and wipe away. For extremely heavy contamination or stubborn deposits, allow the solvent to penetrate thoroughly before wiping the surface clean.

TECHNICAL DATA

Appearance	:	Clear, colourless liquid
Odour	:	Characteristic hydrocarbon
SG@25°C	:	0.823
Pressure @25°C	:	4 bar
Discharge rate	:	1.8g/sec
Solubility	:	Soluble in water and most organic solvents
Flammability	:	Classified as extremely flammable under CHIP Regulations
Packaging	:	400 ml aerosol (12 per carton). Also available in non-aerosol 5Ltr and 25Ltr

STORAGE

The product may be stored at normal ambient temperatures and has a shelf life of not less than 36 months with correct storage. Aerosols should always be stored below 50° C, away from direct heat and naked flame.

HEALTH AND SAFETY

Health and Safety sheet available separately.

TECHNICAL SERVICE

Ambersil provides a technical support service and maintains a constant programme of research and development. We are able to assist customers by specific product development to meet particular requirements.

MISREPRESENTATION ACT 1967 TRADE DESCRIPTIONS ACT 1968

The information given in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which affect the use and performance of our products and for which reason no warranty is given, express or implied. Users should make their own tests to determine the applicability of such information or the suitability of any products for their own particular purposes. Statements concerning the use of the products described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is to be assumed.

CRC Industries UK Limited, Wylds Road, Bridgwater, Somerset, TA6 4DD

Tel: +44 (0) 1278 727200 Fax: +44 (0) 1278 425644 Web: www.ambersilindustrial.com E-mail: salesuk@crcind.com